

CLAIM AMENDMENTS

1.-29. (Cancelled)

30. (Previously Presented) A printed circuit board comprising:

a printed circuit board substrate;

a signal layer supported by the printed circuit board substrate, the signal layer comprising traces to communicate signals not associated with regulated supply voltages;

a supply voltage plane supported by the printed circuit board substrate, the supply voltage plane embedded in the signal layer to supply power to multiple supply voltage pins of a component mounted to the printed circuit board; and

a supply voltage plane layer different from the signal layer, the supply voltage plane layer comprising an embedded ground plane to provide ground connections for the signal layer.

31. (Previously Presented) The printed circuit board of claim 30, wherein the ground connections are associated with electrical devices connected to the component.

32. (Previously Presented) The printed circuit board of claim 30, wherein the ground plane has an outer boundary established by the ground connections.

33. (Previously Presented) The printed circuit board of claim 30, wherein the ground plane lies substantially within a region located directly below the component, the component being mounted on top of the signal layer.

34. (Previously Presented) The printed circuit board of claim 30, wherein the ground plane is significantly larger than the supply voltage plane.

35. (Previously Presented) The printed circuit board of claim 30, wherein the ground plane has an outer boundary that circumscribes a projection of the supply voltage plane onto the supply voltage plane layer.

36. (Previously Presented) The printed circuit board of claim 30, further comprising:
a core layer,
wherein the signal layer and the supply voltage plane layer are located on the same side
of the core layer.

37. (Previously Presented) The printed circuit board of claim 30, wherein the ground
plane reduces an inductance.

38. (Previously Presented) A printed circuit board comprising:
a printed circuit board substrate;
a supply voltage plane layer supported by the printed circuit board substrate, the supply
voltage plane layer to communicate a supply voltage; and
a ground plane supported by the printed circuit board substrate, the ground plane
embedded in the supply voltage plane layer to provide ground connections to multiple pins of a
component mounted to the printed circuit board,
wherein the ground connections are associated with electrical devices connected to the
component.

39. (Previously Presented) The printed circuit of claim 38, further comprising:
a ground plane layer separate from the supply voltage plane layer.

40. (Previously Presented) The printed circuit board of claim 38, wherein the ground
plane lies substantially within a region located directly below the component, the component
being mounted on top of a signal layer.

41. (Previously Presented) The printed circuit board of claim 38, wherein the ground
plane has an outer boundary established by the ground connections.

42. (Previously Presented) A method comprising:
for each high frequency component to be mounted on a printed circuit board, embedding an associated supply voltage plane in a signal layer of the printed circuit board to provide power to the component, the signal layer being used to communicate high frequency signals associated with the high frequency component or components; and
for each supply voltage plane embedded in the signal layer, embedding an associated ground plane in a supply voltage plane layer of the printed circuit board to provide ground connections for the component associated with said supply voltage plane embedded in the signal layer.

43. (Previously Presented) The method of claim 42, further comprising:
providing a core to support the signal layer and the supply voltage plane layer; and
locating the signal layer and the supply voltage plane layer on the same side of the core.

44. (Previously Presented) The method of claim 42, further comprising:
providing a ground plane layer on the opposite side of the core from said same side of the core; and
connecting the ground plane or planes embedded in the supply voltage plane layer to the ground plane layer.